

# HS15

## HS15 Headphones



### Description

After decades of experience in the field of conferencing, the HS15 is the apex of Televic's expertise in headsets.

A sleek design paired with secure, high-quality audio, creates a perfect headset with excellent sound quality and an omnidirectional microphone.

The HS15's optimal adjustment and lightweight design allows hours of use. After the conference, a simple hygienic tissue will prepare the unit for the next user, without the need to exchange expensive foam cushions.

It's flexible enough to achieve different wearing positions. Finally, the cable is very soft and TPU covered to reduce the structure-borne noise.

### Features

- » Wide frequency range
- » Ultra lightweight
- » Wide adjustment range
- » Low impedance technology
- » Integrated clip on front panel
- » The headband is made of soft TPE material
- » Omnidirectional condenser microphone
- » Outstanding sound quality
- » Single 4 pin 3.5 mm jack according to CTIA standard

## Specifications

Mechanical	
Cable diameter	ø 2.5 mm
Jack	ø 3.5 mm stereo, right-angled
Ear caps diameter	ø 53 mm
Ear caps adjustment (via gimbal joint)	± 10° in each direction
Ear pads contact pressure	2.2 N
Adjustment range for head size	63 mm per side
Electrical	
Acoustic	40 mm speaker
Impedance	32 Ω
Sensitivity	98 ±3 dB SPL/mW (@ 32 Ω)
THD @ nominal level	< 1% (@ 1 kHz @ 1 mW)
Frequency Range	20-20,000 Hz
Microphone	
Polar Pattern	Omnidirectional
Audio frequency bandwidth	20 to 20000 Hz
Sensitivity	8.5 mV/Pa
Equivalent noise level	32 dB-A
Electrical impedance	2000 Ω