

# Confidea T-CIV

## Confidea Tabletop Chairman Interpretation Unit & Voting Unit



### Description

The Confidea T-CIV is Televic's tabletop delegate unit for discussion systems combined with simultaneous interpretation & electronic voting. It combines a slim, contemporary design and excellent intelligibility with effortless ease of use.

The unit has a channel selector and two headphone outputs with a single volume control. It allows a meeting delegate to speak, request-to-speak and listen to the speaker in his or her native language, and register his or her vote.

An OLED information display indicates the selected channel number, the abbreviated channel language name in ISO format and a volume bar. This unit is also equipped with an RFID card reader for identification. This is ideal for meetings with a free seating policy: the system can keep track of who is seated where.

The unit has 5 voting buttons. The dedicated CoCon Control Software suite allows for voting applications, preparation of voting agenda, extended voting control, logging and display of voting results.

Compared to the delegate version, this unit has an additional priority, next-in-line and system volume adjustment button.

The units interconnect in daisy chain over Cat 5e Plixus® network cabling. The RJ45 connectors are hidden in the base of the unit and the cables are held in place by two notches in the unit housing.

### Benefits

The Confidea T-CIV is a sleek and stylish solution and can be set up in the blink of an eye. The input and output connections are auto-sensing and interchangeable. As a result, installation is easy, fast, and straightforward, making it the ideal system for frequently changing environments.

The removable microphone is immune for mobile phone interference, so delegates can leave their phones switched on during the meeting. The Confidea T-CIV is backed by the Plixus® network with redundant cabling and hot swapping options to ensure maximum reliability. Finally, its shielded microphone is immune to mobile phone interference.

## Features

- » Built-in high-quality loudspeaker which is automatically muted when the microphone is active, to prevent acoustic feedback
- » Microphone On/Off or request-to-speak button with two signaling LEDs
- » Two headphone outputs with single volume control
- » Next-in-line button
- » Priority button
- » Five voting buttons (++/+0/-/-)
- » OLED information display with selected language and volume bar
- » RFID card reader

## Connectivity

- » Screw-lock socket to connect a removable microphone.

<b>D-MIC30SL</b>	<b>71.98.0053</b>
<b>D-MIC40SL</b>	<b>71.98.0054</b>
<b>D-MIC50SL</b>	<b>71.98.0055</b>

- » Two RJ 45 connectors for loop through cabling
- » Two 3.5 mm stereo jack sockets for headphones
- » Plixus-powered

## Software

- » To fully configure, manage, and use the unit, Televic's CoCon management software is required. The following standard licenses are available:

<b>CoCon Discussion</b>	<b>71.98.1101</b>
<b>CoCon Signage</b>	<b>71.98.1102</b>
<b>CoCon Voting</b>	<b>71.98.1104</b>
<b>CoCon Authentication</b>	<b>71.98.1105</b>
<b>CoCon Interpretation</b>	<b>71.98.1107</b>

## Certification

Region	Certification
Europe	CE

## Specifications

Mechanical	
Material	PC/ABS
Color	Black Matt, RAL9011
Size (mm)	230 (w) × 130 (h) × 60 (d)
Size packed (mm)	250 (w) × 150 (h) × 90 (d)
Weight	480g
Weight packed	620g
Electrical	
Voltage	48 VDC
Consumption	4.5 W
Card reader	ISO 14443 MIFARE Card Reader DESfire EV1 support
Speaker Output	
Maximum output power	> 1 W
Frequency response	200-20,000 Hz
Dynamic range	> 90 dB
THD @ nominal level	< 0.1 %
Load impedance	8 Ω
Headphone Output	
Maximum output	> 10 mW
Frequency response	22-22,000 Hz
Dynamic range	> 90 dB
THD @ nominal level	< 0.1 %
Load impedance	16-32 Ω
Microphone Input	
Nominal input level	-54.7 dBV
Maximum input level	-24.6 dBV
Input impedance	1 kΩ
Dynamic range	> 93 dB
Frequency response	25-20,000 Hz
THD @ nominal level	< 0.1 %